




Specifications

- bottom mount
- 24 mm
- dynamic up to 120 kg (full extension)
- dynamic up to 105 kg (over extension)
- dynamic up to 90 kg (heat-resistant)
- solid synthetic rollers
- stainless steel 1.4509 / 441
- 25 °C to +80 °C

Characteristics

- high lateral stability
- cabinet profile with screw holes and drawer profile without holes
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- self-closing
- available as heat-resistant version up to +110 °C – load capacity for full extension 90 kg

Dimensions



Length	Extension		Weight	Item No.	Item No.	Item No.
	full extension	over extension				
mm	mm	mm	kg			
400	385	460	3.51	▶ 7130	▶ 7140	*
450	435	510	4.00	▶ 7131	*	*
500	485	560	4.44	▶ 7132	▶ 7142	*
550	535	610	4.86	▶ 7133	▶ 7143	*
600	585	660	5.28	▶ 7134	▶ 7144	*
650	635	710	5.77	▶ 7135	▶ 7145	*
700	685	760	6.37	▶ 7136	*	▶ 82561
750	735	810	7.00	▶ 7137	*	*

Packing Unit – Sets per Box: from 400 to 600 mm: 4 | from 650 to 750 mm: 2

▶ in stock | * on request